

Review article

Available online www.ijsrr.org

ISSN: 2279-0543

International Journal of Scientific Research and Reviews

Heavy Metal Removal from Aqueous Solution Using Zeolite (A Review)

Nigam Mohit *, Dubey Nidhi, Khan Salman, Beena and Kumar Anil

Raja Balwant Singh Engineering Technical campus, Bichpuri, Agra, U.P. INDIA

ABSTRACT

The removal of pollutants from water and wastewater is a problem that has grown with rapid industrialization. Due to extensive anthropogenic activities such as industrial operation particularly mining, agriculture processes and disposal of industrial waste material; their concentration has increased to dangerous levels. Heavy metals in industrial effluent include nickel, chromium, lead, zinc, arsenic, cadmium, selenium and uranium. Many methods are used for the removal of heavy metals such as ion exchange, reverse osmosis chemical precipitation, electro dialysis, ultra filtration, nano filtration, coagulation, flocculation, floatation etc. But these methods have many disadvantages like high reagent requirement, unpredictable metal ion removal, generation of toxic sludge etc. Adsorption is recognized as an effective and economic method for low concentration heavy metal wastewater treatment. The natural Zeolites could adsorb and remove the heavy metals in the aqueous solutions. This paper reviews the use of synthetic zeolite as an adsorbent for the removal of heavy metals from aqueous solution. The critical parameters affecting the adsorption of heavy metal ions are investigated by utilizing zeolite NaX as the potential adsorbent. The adsorptions of heavy metal ions are strongly dependent on pH, temperature, contact time and initial adsorbate condition. The aim of this study was determining the removal efficiency of zeolite for removing heavy metals from aquatic solutions.

KEY WORDS-

Heavy metal, adsorption, zeolite NaX, adsorbent.

Corresponding Author:-

Er. Mohit Nigam, Asst. Professor, Raja Balwant Singh Engineering Technical campus Bichpuri, Agra. E-mail:- <u>mohitnigam2012@gmail.com</u> Mob. No. +918923574833

INTRODUCTION

Water contaminated by heavy metal ions had become much more serious with a rapid development of industries and competitive use of fresh water in many parts of the world¹. "Heavy metals" is a general collective term applied to the group of metals and metalloids with an atomic density greater than 6 gm⁻³ include such elements as Cd, Cr, Cu, Hg, Ni, Pb, and Zn which are commonly associated with pollution and toxicity problems. These pollutants reach the environment from the vast array of anthropogenic sources as well as natural geochemical process². The release of heavy these metals into the environment through industry effluents is a major concern, worldwide and removal of such pollutants has been a great concern during last decades. These heavy metals are non-biodegradable which leads to several health problems in animals, plants and human beings such as cancer, kidney failure, metabolic acidosis, oral ulcer, renal failure and damage in stomach of the rodent^{3,4}. Therefore, the removal of heavy metal ions from water has become an important subject today. Several conventional methods exist for the removal of heavy metal pollutants from wastewater. These methods include precipitation, electroplating, chemical coagulation, ion-exchange, membrane separation, and electro kinetics⁵. However, most of these methods have limitations, which include high cost, unavailability, and generation of large volumes of secondary waste and poor removal efficiency. Considering from the economy and efficiency point of view, adsorption is regarded as the most promising and widely used method among all these⁶. The efficiency of adsorption depends on many factors, including the surface area, pore size distribution, polarity, and functional groups of the adsorbent⁷. The selectivity series of clinoptilolite in the sodium form was determined by Zamzow et al., as follows: $Pb^{2+} > Cd^{2+} > Cs^+ > Cu^{2+} > Co^{2+} > Cr^{3+} > Zn^{2+}$ $> Ni^{2+} > Hg^{2+8}$. Zeolites are crystalline alumino-silicates having uniform cavities and having strong ion-exchange capacity. The substitution of aluminium for silicon results in a residual negative charge density, which is balanced by the presence of other metallic ions in the pores of the framework. Due to their structural characteristics, zeolite can be used in several applications⁹.

The objective of the present study is to investigate the adsorption potential of on synthetic zeolite in the removal of heavy metal ions from aqueous solution. The effects of pH, adsorbent dosage, contact time and temperature on adsorption capacity of synthetic Zeolite have been investigated. The Langmuir and Freundlich isotherms models are applied to the sorption data to calculate the different parameters and the best fitting achieved. The pollution of water resources due to the disposal of heavy metals has been an increasing worldwide concern for the last few decades. The removal of pollutants from water and wastewater is a problem that has grown with rapid industrialization. The discharge of toxic metals into water sources is a serious pollution problem,

which may affect the quality of water supply. By confirming the toxic effects of these metals, various methods have been implemented to remove pollutants from aqueous solutions. The aim of this study was determining the removal efficiency of synthetic zeolite for removing heavy metals from aqueous solutions.

TOXIC HEAVY METALS

Pb⁺², Cu⁺², Fe⁺³ and Cr⁺³ are especially common metals that tend to accumulate in organisms, causing numerous diseases and disorders¹⁰. They are also common groundwater contaminants at industrial and military installations. Numerous processes exist for removing dissolved heavy metals, including ion exchange, precipitation, phytoextraction, ultrafiltration, reverse osmosis, and electro dialysis^{11,12}. Copper is one of the most important metals often found in industrial effluents such as acid mine drainage, galvanizing plants, natural ores and municipal wastewater treatment plants. It is not biodegradable and it travels through the food chain via bioaccumulation¹³. Removal of copper from waste water is crucial and its toxicity for human beings is at levels of 100-500 mg per day^{14,15}.

SOURCES AND CAUSES OF DIFFERENT HEAVY METALS

Heavy metal	Sources	Causes	Guideline value	References
			(mg/L)	
Copper	Making pipes,	Mucosal irritation,	2.0	16,17
	valves, fitting,	widespread capillary		
	coating sand	damage, hepatic and		
	alloys, copper	renal injury, central		
	jewellery, copper	nervous system irritation		
	cooking pots,	followed by depression,		
	alcoholic	gastrointestinal irritation,		
	beverages from	necrotic changes in the		
	copper brewery	liver and kidney.		
	equipment, instant			
	gas hot water			
	heaters, hormone			
	pills.			

Inorganic mercury	Electrolytic production of chlorine, in dental amalgams, electrical appliances.	Tremorors, birth defects, kidney damage, nausea, loss of hearing or vision, gingivitis, chromosome damage, mental retardation, tooth loss,	0.006	17,18
		hypertonia- muscle rigidity, minamata disease.		
Chromium	Steel and textile industry	Skin rashes, respiratory problems, haemolysis, acute renal failure, weakened immune systems, kidney and liver damage, alteration of genetic material, lung cancer, Pulmonary fibrosis.	0.05	17
Nickel	Production of stainless steel, nickel alloys, effluents of silver refineries, electroplating, zinc base casting and storage battery industries.	Skin irritation, damage to the lungs, nervous system, mucous membranes, dizziness, nausea, vomiting, chest pain, rapid respiration.	0.07	17
Cadmium	Contamination from fertilizers	Kidney and tubular cells damage	0.003	17
Lead	Storage batteries, gasoline additives, ammunition: shot and bullets, solder	Irreversible brain damage, injury to the blood- forming systems, nervous system damage	0.01	17

Nigam Mohit et al., IJSRR 2015, 4(2), 17 - 27

RESULTS & DISCUSSION

Adsorbent	Heavy Metal	Removal Efficiency (%)	рН	Adsorption capacity (mg/g)	Contact time (min)	Initial Concentration (mg/l)	Reference
Nanozeolite	Cr(VI)	45	3	14.16	60	1	19
Zeolite NaX	Cr(VI)	44.40	4	6.414	120	10	20
Activated carbon	Cr(VI)	98.10	2	9.00	600	500	21,22
Clinoptilolite	Cu(II)	89.62	4	0.24	75	2.748	23
Scolecite natural zeolite	Cr(VI)	85	6.5	0.75	120	20	24
Agriculture wastes carbon	Cr(VI)	91.75	2	59.23	120	250	25
Natural zeolite zlatokopmine, Serbia	Cu(II)	18.6	7	8.3	200	100	26

Table2: Data from various studies with the subject "Removal of Heavy Metals from Aqueous solutions"

Effect of pH:-

pH is one of the most important parameters controlling uptake of heavy metals from wastewater and aqueous solutions. Removal efficiency for natural pH was obtained 15.38% and minimum removal efficiency was 7.69%. In the studies, the percentage adsorption increased with increasing pH to reach a maximum at pH 6 & then, it decreased with further increase in pH^{27} .

The mechanism of adsorption at the zeolite NaX surface reflects the nature of physicochemical interaction of the metal ions in the solution and the active sites of the zeolite NaX. The uptake capacity of zeolite NaX is found maximum at pH 6.0. The removal of metal ions is strongly dependent on the pH of the solution²⁸.

Effect of temperature:-

In E. Muzenda et al.'s study, the effect of temperature on adsorption of copper(II) ions was investigated by varying temperature from 30-90^oC at various initial concentration at a pH of 4 for 24

hr. and adsorption was found to be temperature dependent. At higher temperature zeolite pore sizes could increase enhancing the rate of intrapartical diffusion of ions²⁹.

In Pankaj pandey et al.'s study effect of temperature on adsorption of copper (II) ions is studied by conducting different sets of experiment at initial concentration of 25ppm at different temperature i.e. 288,303,323 K. It is observed that adsorption of copper ions increases with increase in the temperature⁹.

Effect of Contact Time:-

The percent removal of heavy metal increases by increase of contact time till equilibrium is attained. The removal of copper (II) ions is high in the first 10 min. and then, the rate significantly decreases and eventually approaches zero, and finally the equilibrium point has been attained³⁰. From V.O. Vasylechko et al.'s study, the removal of copper (II) ions increased with time and attained saturation in about 60-70 min.³¹.

Pankaj pandey et al.'s the removal of copper(II) increases with time and attains saturation in 60-120 min. The removal rate of adsorption is rapid initially but it gradually decreases with time until it reaches equilibrium⁹.

The Effect of Initial Concentration of Heavy Metal:-

The effect of initial concentration on removal efficiency that by increasing initial concentration of heavy metal, the removal efficiency decreased. From Samarghandi MR et al.'s study the percentage of Cr(VI) removal decreased from 99.37-40.24% by increasing the initial Cr(VI) concentration from 20 -100 mg/l .the decrease in the percentage removal can be explained by the fact that the adsorbent had a limited number of active sites; which would have become saturated above a certain concentration³².

The Effect of Zeolite Concentration:-

Adsorption increased with increase in zeolite amount for fixed initial concentration, this is because the increase in zeolite amount leads to increase adsorption surface area and available active sites³³.

ADSORPTION ISOTHERMS

The adsorption isotherms are very important in describing the adsorption behaviour of solutes on the specific adsorbents. In these studies, two important isotherm models such as Langmuir and Freundlich were selected and studied.

Langmuir adsorption isotherm is the most popular and is a two-parameter equation. Langmuir sorption isotherm models the monolayer coverage of the sorption surfaces and assumes that sorption occurs on a structurally homogeneous adsorbent and all the sorption sites are energetically identical. The general form of Langmuir isotherm is as follows-

$$C_{e}/Q_{e} = 1/(Q_{m}b) + C_{e}/Q_{m}$$

Where costants b and Q_m relate to the energy of adsorption and adsorption capacity and their values are obtained from the slope and intercept of the plot of Ce/Qe versus Ce. If the plot is linear it shows that the adsorption follows the Langmuir isotherm. The value of b, which is a measure of heat of adsorption, is utilized to calculate dimensionless separation parameter RL^{34} .

The Freundlich expression is an empirical equcation based on a heterogeneous surface³⁵. This isotherm is the earliest known relationship and described by the following equcation:

$$\text{Log } Q_e = \log K + 1/n(\log C_e)$$

Where K and n are Freundlich constants which correspond to adsorption capacity and adsorption intensity respectively. The slope (1/n) and intercept (K) of a log-log plot of Qe versus Ce are determined.

CONCLUSION:-

From various studies we concludes some results which are as follows -

- 1) The removal efficiency is increased with increase in pH. The maximum of removal efficiency was occurred at pH 6 and then, it decreased with further increase in pH.
- 2) Adsorption of ions increases with increase in the temperature.
- 3) With increasing time to reach equilibrium time, the removal efficiency was increased.
- 4) Percentage removal of ions decreases with increase in initial metal concentration.

According to these results, it can be concluded that the zeolite is a good absorbent for removal of heavy metals ions from aqueous solution.

REFERENCES:-

[1]. Ahmadi SJ, Sadjadi S, Hosseinpour M. Adsorption behavior of toxic metal ions on nano structureCuOgranules.SeparSciTechnol.2012; 47:10631069.

[2] A Mark. Keane. The Removal of Copper and Nickel from Aqueous Solution Using Y Zeolite Ion Exchanger. Physicochemical and Engineering Aspects.1998; 138:11-20.

[3] M.Malakootian, J.Nouri, and H Hosaini. Removal of Heavy Metals from Paint Industry's Wastewater Using Leca as an Available Adsorbent. Int. J. Environ. Sci. Tech.2004; 6(2):183-190.

[4] K. Shaila, P. Deepa, and P. Pralhad. Synthesis of Zeolite using Fly ash and its application in Removal of Cu^{2+} , Ni^{2+} , Mn^{2+} from Paper Industry Effluent. Research J. Of Chemical Sciences.2014; vol. 4(3), pp. 5–9.

[5] S M Shaheen, A. S Derbalah, and F S Moghanm. Removal of Heavy Metals from Aqueous Solution by Zeolite in Competitive Sorption System. Int. J. Environ. Sci. Dev.2012; vol. 3(4), pp. 362–367.

[6] Kang KC, Kim SS, Choi JW, Kwon SH. Sorption of Cu^{2+} and Cd^{2+} onto acid and base pretreated granular activated carbon and activated carbon fiber samples. J Ind Eng Chem. 2008, 14:131–135.

[7] Ewecharoen A, Thiravetyan P, Wendel E, Bertagnolli H.Nickel adsorption by sodium polyacrylate-grafted activated carbon. J Hazard Mater 2009; 171:335–339.

[8] E. Erdem, N. Karapinar, and R. Donat. The removal of heavy metal cations by natural zeolites. J. Colloid Interface Sci.2004; vol. 280(2), pp. 309–314.

[9] P. Pandey, S. S. Sambi, S. K. Sharma, and S. Singh. Batch Adsorption Studies for the Removal of Cu (II) Ions by Zeolite NaX from Aqueous Stream. vol. I, no. Ii, 2009.

[10] V.J. Inglezakis, M.D. Loizidou, H.P. Grigoropoulou. J. Colloid Interface Sci. 261 (2003) 49.[11] L.E. Applegate. Chem. Eng. 91 (1984) 64.

[12] J.L. Schnoor, Phytoremediation.Ground-Water Remediation Technologies Analysis Centre. Pittsburgh .TE-97-01; 1997.

[13] T. Akar and S. Tunali. Biosorption performance of Botrytis cinerea fungal by-products for removal of Cd (II) and Cu (II) ions from aqueous solutions. Mineral Engineering.2005; vol. 18, pp. 1099-1109.

[14] L. Norton, K. Baskaran, and T. McKenzie. Biosorption of zinc from aqueous solutions using bio solids. Advances in Environmental Research.2004; vol. 8, pp. 629-635.

[15] K. Chong and B. Vole sky, Description of 2- metal bio sorption equilibrium by Langmuir- type models. Biotechnology. Bioeng.1995; vol. 47, 451-460.

[16] Argun ME, Dursun S, Ozdemir C, Karatas M. Heavy metal adsorption by modified oak sawdust. Thermodynamics and kinetics. J Hazard Mater 2007; 141(1):77-85.

[17] WHO. Guidelines for Drinking-water Quality.3rd ed.Geneva: WHO; 2006.

[18] Raji C, Anirudhan T. Chromium (VI) adsorption by sawdust carbon. Kinetics and equilibrium. Indian J Chem. Technol. 1997; 4(5):228-36.

[19] Tashauoei, et al. Removal of hexavalent chromium (VI) from aqueous solution using surface modified nanozeolite A. Int. J. Environ. Res.2010; 4 (3):491-500.

[20] P.K Pandey, et al. Kinetics and equilibrium study of chromium adsorption on zeolite NaX .Int.J. Environ. Sci. Tech.2010; 7(2), 395-404.

[21] Hakan Demiral, et al. Adsorption of chromium (VI) from aquieous solution by activated carbon derived from olive bagasse & applicabilitity of different adsorption models. Chemical engineering journal 2008; 144:188-196.

[22] Muataz ali atieh, et al. Removal of chromium (VI) from polluted water using carbon nanotubes supported with activated carbon. Procedia environmental sciences. 2011; vol. 4,281-293.

[23] Edition Muzenda, et al.Cupper (II) Removal from synthetic waste water by ion exchange process.Cr (VI) From aqueous solution by scolecite natural zeolite.Int. J. Chem. Sci.2012; 10(2).

[24] Bhagyashree salunkhe and Sunita J. Raut. Removal of heavy metal Ni(II) and Cr(VI) from aqueous solution by scolecite natural zeolite. Int. J. Chem. Sci.2012; 10(2).

[25] Manjeet Bansal, et al. A comparative study for the removal of hexavalent chromium from aqueous solution by agriculture waste carbon. J. Hazard Mater. 2009.

[26] JelenaMilenKovic, et al.Copper removal from aqueous solution using natural zeolite and antibacterial activity of the copper-loaded zeolite, proceeding of the 4th Slovenian-Croation Sympocium on zeolite.

[27] Karthikeyan T et al.; Chromium (VI) adsorption from aqueous solution by Hevea Brasilinesis sawdust activated carbon. J Hazard Mater 2005; 124(1-3):192-9.

[28] Biskup B. et-al. Removal of heavy metal ions from solutions using zeolite: influence of sodium ion concentration in the liquid phase on the kinetics of exchange processes between cadmium ions from solution and sodium ion from zeolite A. Sep. Sci. and Tech.2004; vol.39, pp.925-940.

[29] E. Muzenda et al. Cu(II) Removal from synthetic waste water by ion exchange process,vol, II, no. Ii, 2011.

[30] Acar FN et al. Removal of Cu (II) ions by activated popular sawdust (Samsun Clone) from aqueous solutions. J Hazard Mater.2006; 137(2):909-14.

[31] V.O. Vasylechko et al.; Investigation of usefulness of Transcarpathian zeolites in trace analysis of waters. Application of mordenite for the pre concentration of trace amounts of copper and cadmium, Chem. Anal. (Warsaw).1999; vol. 44, no. 6, pp. 1013-1024.

[32] Samarghandi MR et al. Removal of divalent nickel from aqueous solution by adsorption onto modified Holly. Iran J Environ Health Sci Eng 2011; 8(2):181-188.

[33] H. Dyer, The plotting and interpretation of ion- exchange isotherms in charcoal systems. Sep. Sci. Technol.1981; vol. 16, pp. 173-183.

[34] T.W.Weber, R.K. Chakraborti. Pore and solid diffusion models for fixed bed adsorbents. J. AIChE 20.1974; 228-238.

[35] Langmuir I. The constitution and fundamental properties of solids and liquids. Part I: solids. J Am Chem Soc. 1916; 38:2221–2295. doi: 10.1021/ja02268a002.